

Pionite[®] Backing Sheets are applied to the back of a substrate that is faced with a high pressure decorative laminate. With proper application, Backing Sheets will provide dimensional stability to the assembly, reducing the likelihood of warpage. Pionite Backing Sheets are phenolic laminate that are not intended for decorative surfacing. A slight variation in color is normal and should be anticipated. Backing Sheets are available in either brown or black. Backing Sheets are normally sanded on one side, however, both sides can be sanded. Pionite[®] Fire Rated Backing Sheets are also available.

Product Description

Type	Standard Nominal Sizes		
	Thickness*	Width	Length
B20 (in)	0.020	36, 48, 60	96, 120, 144
(mm)	0.5	914, 1219, 1524	2438, 3048, 3658
B28 (in)	0.028	36, 48, 60	96, 120, 144
(mm)	0.7	914, 1219, 1524	2438, 3048, 3658
B37 (in)	0.038	36, 48, 60	96, 120, 144
(mm)	1.0	914, 1219, 1524	2438, 3048, 3658
B48 (in)	0.048	36, 48, 60	96, 120, 144
(mm)	1.2	914, 1219, 1524	2438, 3048, 3658

*Other widths and thicknesses of Backing Sheets are available upon request.

Typical Uses

Backing Sheets applied to substrates faced with Pionite[®] high pressure decorative laminate impart stability and reduce the likelihood of warpage to the final product. For best results, the backing sheet thickness should be relatively equal to that of the decorative laminate on the face of the assembly. For this reason, many thicknesses of backing sheets are offered.

Codes and Certifications

1. U.S. Federal Specification L-P-508H, "Plastic Sheet, Laminated, Decorative and Nondecorative." Pionite Type B20, B28, and B48 comply.
2. American National Standards Institute/National Electrical Manufacturers Association (ANSI/NEMA), LD3-2005, "High- Pressure Decorative Laminate." Pionite Type B20, B28, B37, and B48 comply.

Fabrication Tips

When working with Backing Sheets, these techniques will produce a quality application.

1. Proper conditioning of the laminate, substrate, and backing sheet minimizes possible warping, shrinking, or expansion of assembled panels. Ideally, all components should be conditioned at 70 °F to 75 °F (21 °C to 25 °C) and 45 to 50 percent relative humidity for 48 hours prior to assembly.
2. Always bond backer to a suitable substrate such as medium to high density fiberboard, particleboard, or metals. It should not be glued directly to plaster walls, gypsum wallboard, or concrete.
3. Recommended adhesives include solvent or water-based contact cement, white glue (PVA), epoxy, and hot melt glue. Consult your adhesive supplier for specific application requirements.
4. All saw blades and router bits used for cutting should be carbide tipped. Feed rate should be slow and tool speed should be high.
5. Inside corners of cutouts for electrical outlets, sinks, etc., should have a minimum radius of 1/8" (3 mm) and be filed smooth. This reduces the likelihood of stress cracks.
6. All edges of backer should be filed smooth to help prevent stress cracks and to minimize chipping.
7. When fasteners must be used, it is advisable to first drill an oversized hole through the backer. This reduces the likelihood of stress cracks.
8. All laminate is intended for interior use only, and should not be exposed to extreme humidity, continuous sunlight, or temperatures above 275 °F (135 °C) for extended periods of time.

Limited Warranty

Subject to the limitations set forth below, Panolam® Industries International Inc. (Panolam) expressly warrants that our products are reasonably free of defects in material and workmanship, and when properly handled and fabricated will conform, within accepted tolerances, to applicable manufacturing specifications as set forth in our technical brochure. This warranty shall extend to the original buyer for a period of twelve (12) months from the date of shipment of this product by Panolam, and shall not be assignable by the original buyer. This warranty does not cover damage resulting from accident, misuse, alteration, abuse or lack of reasonable care.

Due to the variety of uses and applications to which this product may be put, and because the manufacturer has no control over the end products fabricated, the warranty set forth above is exclusive and in lieu of all warranties, expressed or implied, in fact or by operation of law or otherwise, or arising by course of dealing or performance, custom or usage in the trade, including, without limitation, the implied warranties of fitness for a particular purpose and merchantability, and Panolam shall have no obligation or liability to any person or entity in connection with or arising from the furnishing, sale, installation or repair, use or subsequent sale of any product supplied by it.

Our maximum liability arising out of the sale of the products or their use, whether based upon warranty, contract, tort or otherwise, shall not exceed the actual payments received by us in connection therewith. In no event shall we be liable for special, incidental or consequential damages, including, but not limited to, arising hereunder or from the loss of profits, or loss of use damages, sales of the products.

Headquarters

Panolam® Industries International, Inc.

20 Progress Drive

Shelton, CT 06484

1-877-726-6526

www.panolam.com



© 2016 Panolam Industries International, Inc.

1/2016