


FRL®

FRL® panels are an innovative wall and door surfacing product from Panolam.

Engineered and manufactured to exacting standards, FRL decorative surfaces provide high-impact protection with a wear resistance that is 23 times higher than rigid vinyl. It is also Class A Fire Rated and substantially lower smoke and flame spread than other competitive products.

See what makes our FRL Wall Protection Panels so unique:



FRL Panel Highlights

- Class A Fire Rated
- Classification based on UL approved substrate and glue being used
- High-impact strength
- Chemical resistant surface (SEFA 8 compliant)
- Exceptional cleanability without harsh chemicals
- Extraordinary wear protection
- Available in over 250+ Nevamar colors and patterns
- Can be laminated to various substrates
- NSF approved for horizontal and vertical applications
- UL/ULC Certification
- Can be ordered as IMO Certified. FRL surfaces have been tested in accordance with the International Maritime Organization (IMO) A.653(16) And meets Parts 2 and 5 of Annex 1 of the IMO FTP Code.



Inspira™ Digital Graphics
Panolam can expand your creative vision with in-house custom digital graphics. Whether your design calls for a unique photo, company logo or one-of-a-kind illustration, Panolam has the skill and technology to bring your ideas to life. Ideal for wall murals, feature walls, headwalls, school logos, wayfinding and elevator cabs.

Whether it's guarding against shopping carts in a grocery store, gurneys bursting through trauma center doors, or the exuberant play of pre-school students in their classrooms, the superior performance of Panolam's FRL panels will withstand it all while maintaining its pristine appearance.

This product is also available as IMO Certified for use in Marine applications.

FACILITIES

- Hospitals
- Schools/Universities
- Restaurants/Dining halls
- Supermarkets
- Airports
- Lab/Clean rooms
- Daycare centers
- Nursing homes/Assisted living
- Hotels/Casinos/Resorts
- Retail environments
- Spas/Health clubs

APPLICATIONS

- Wainscoting/Wall cladding
- Retail areas/Checkout areas
- Headwalls in patient rooms
- Corridors
- Doors/Kickplates
- Elevator cabs
- Lobbies
- Restrooms/Toilet partitions
- Commercial kitchens
- Transit systems: bus, subway, rail
- Boat/RV interiors

Finish Options

FRL panels are available in six different finishes designed to enhance the look and texture of any project. For quicker processing of your sample request, kindly use the designated finish code at the end of the pattern code number. Please contact your local Nevamar® representative or visit nevamar.com for finish samples, grade and sheet availability.

Ashwood (AW)* is a fine wood finish with a cathedral grain.

Crystal (CR)* is a fine pebble grained finish with a medium gloss.

LineZ (LZ)* is a deeply embossed, linear woodgrain finish.

Soft Leather (LR)* is a finely grained leather finish.

Suede (SD) is a low gloss, textured finish.

Wood Essence (WE)* is a natural-appearing, linear woodgrain finish.

*An additional charge applies

Sheet Size Availability

Suede (SD), Crystal (CR), Soft Leather (LR), Ashwood (AW) and Wood Essence (WE) are available in 3', 4' & 5' widths x 8' & 10' lengths.

Line Z (OZ) is available standard in 4' x 8'.

Other sizes are available on a project by project basis.

All carry a five (5) sheet minimum of a color and size.


Environmental Features

Make Nevamar FRL panels your first choice when specifying materials.

- Low VOCs and GREENGUARD® certified
- By formulating our own resins, we can assure you of an eco-conscious manufacturing process
- Manufactured with decorative paper from recycled or renewable sources to help preserve our forests and promote a healthier environment
- Distribution centers are strategically located across the country to reduce the use of fossil fuels when delivering our products
- Does not support bacterial growth (mold/mildew)



FRL
Fiber Reinforced Laminates



The Nevamar® Surface Systems story

How it all works together:

Multiple Surfaces. One System.

Our goal is to help bring your vision to reality without compromise. As your full surface solution provider, we are here to help navigate the many design and substrate options available to help you achieve your desired aesthetic, performance, and budgetary attributes for every project.

Wall Protection Panels
Learn more at nevamar.com

Technical Information


Technical information listed below applies to Nevamar FRL panels. PDF files of specification sheets/technical data are also available at nevamar.com. Refer to technical bulletin for fabrication requirements and other updated information. For additional information, contact your sales/specification representative or your local distributor.

PHYSICAL PROPERTY	TEST	STANDARD	TYPICAL	FRL
Nominal Thickness	NEMA LD 3-2005 3.13	not applicable	.075"	
Surface Burning Characteristics	ASTM E84	Class C	Class A*	
Wear Resistance (cycles)	NEMA 3.13	≥ 400	3500	
Flexural Strength	ASTM D790	≥ 12,000 psi	22,000 psi	

*Classification based on UL approved substrate and glue being used.

Molding Profiles

Installations can be completed with easy-to-use seam treatments. Available in aluminum and several color coordinated PVC moldings. Color matched silicone caulking is also available. Moldings are sold in 10' lengths. Molding profiles are not shown at actual size.




XCF-000
Outside Corner Flat



XCR-000
Outside Corner Round
2-piece kit



XDB-000
Division Bar
2-piece kit



XIC-000
Inside Corner
2-piece kit



XSC-000
Standard End Cap
2-piece kit



XFB-0000
One Piece
Flat Division Bar

For additional information on FRL Wall Protection Panels, please contact your Nevamar sales representative or local distributor.



ONE CORPORATE DRIVE, SUITE 725
SHELTON, CT 06484 | 877.726.6526
PANOLAM.COM

© 2020 Panolam Industries International, Inc.
Printed in the U.S.A.
NSMPBRFLI-00019-1/20